

CDM6490F



HYDRAULIC EXCAVATOR



LONKING (FUJIAN) INTERNATIONAL TRADE CO.,LTD.

Add: 26 Minyi Road, Xinqiao, Songjiang Industrial Zone, Shanghai
E-mail: export@lonking.cn <http://www.lonkinggroup.com>
Tel: +86-21-3760 2242

- **OPERATING WEIGHT:** 50500kg
- **ENGINE POWER:** 280kW
- **BUCKET CAPACITY:** 2.6m³
- **TRAVEL SPEED:** 3.4/5.3km/h



TECHNICAL PARAMETERS

	Name	Data
Basic	Operating weight	50500 kg
	Boom length	7000 mm
	Arm length	3000 mm
	Standard bucket	2.6 m³ (Rock)
	Max.Travel speed	3.4/5.3 km/h
	Max.Swing speed	8 rpm
	Grade ability	35°(70%)
	Ground pressure	87.1 kPa
	Max.Traction force	396 kN
Engine	Engine model	QSM11-C375
	Rated power	280kW/2000 rpm
	Max.Torque	1898/1400 N.m/rpm
	Displacement	15.681 L
	Fuel tank	680 L
Hydraulic	Max.Flow(total)	360×2 L/min
	Max.Working pressure	34.3 MPa
	Max.Pilot pressure	3.9 Mpa
	Max.Arm digging force	245 kN(ISO)
	Max.Bucket digging force	287 kN(ISO)
	Hydraulic oil tank	480 L
Chassis	Track width	600 mm
	Track shoes number	50(each side)
	Carrier rollers number	2(each side)
	Track rollers number	9(each side)
Electric	System voltage	24 V
	Battery capacity	24 V 200 Ah×2

PRODUCT FEATURES

Cummins Turbocharged Engine, Large Displacement, Strong Power.
Adopt Independent Cooling System to Reduce Power Loss and Noise
Advanced Hydraulic System
Combined C type closed frame improves rigidity and strength of rotary platform.
Comfortable ROPS Cabin with 2.7m ³ Operational Space
No Frame Cab Glasses to Enlarge Operation Field of View
Double-rib Rock Track Shoes, Chassis Reinforcement, More reliable and Wear-resistant
Heavy-duty Working Device with High Strength Low Alloyed Steels

OPTIONAL

Breaking hammer & pipeline
Work warning light
Walking alarm
Top protecting net
Front protecting net
700mm triple grouser shoes
800mm triple grouser shoes

The following blank can be used for notes or comments

For more information on Linking products, please contact our local agent: